

PRODUCT NAME

Custom Printed BOPP Tape

ADHESIVE TYPE

Water / Solvent Acrylic

TENSILE STRENGTH

70 – 80 N / 25mm

MOQ

5,000 Rolls

TECHNICAL SPECIFICATIONS & PERFORMANCE

SPECIFICATION ITEM & DETAILS		PERFORMANCE & OPERATIONAL VALUES	
Brand Name	Krytape	Adhesive Type	Water-based / Solvent-based Acrylic
Place of Origin	Dongguan, Guangdong, China	Tape Thickness	35µm – 80µm (Common: 40, 45, 50, 65, 68µm)
Backing Material	BOPP Film (Waterproof Pressure Sensitive)	Tensile Strength	70 – 80 N / 25mm
Tape Width	24mm, 36mm, 48mm (2"), 60mm, 72mm (3")	Elongation at Break	≤ 120% at break
Tape Length	10m – 1000m (Common: 100y, 300y, 1000y)	Application Temp	-30°C to +40°C
Core Diameter	Inside 76mm (3") Core (Blank / Printed Logo)	Special Function	Low Noise, No Bubble, Easy Tear
Color & Printing	Clear, Tan, White, Custom Pantone & Logo	Certifications	ISO9001:2015, SGS, ROHS, BSCI, SMETA
Minimum Order (MOQ)	5,000 Rolls	Daily Capacity	150,000 Rolls / Day

KEY PERFORMANCE ADVANTAGES

- Low Noise & Easy Tear:** Engineered for quiet unwind, zero bubbles, and smooth manual or automatic dispensing.
- Wide Temperature Range:** High-tack performance remains reliable under harsh temperature conditions (-30°C to +40°C).
- High Tensile Hold:** 70–80 N/25mm tensile strength ensures reliable carton sealing without snapping.

OEM & DIRECT FACTORY CAPABILITIES

- Custom Branding:** Precision logo rotogravure printing, customized paper cores, and branded packaging boxes.
- Mass Production Supply:** Daily capacity of 150,000 rolls supplying global e-commerce and logistics networks.
- Flexible Slitting:** Custom conversion for 100y, 300y, and 1000y jumbo roll dimensions according to demand.

Notice & Technical Guidelines: The values listed above are representative average test results obtained under controlled laboratory conditions in accordance with industry standards and are intended solely as a technical reference guide for standard B2B industrial applications.